

1: IDENTIFICATION

GRADE: SC-24 **Data:** 27/05/2015
SCOPE: Describe product composition, characteristics and other valuable information
PRODUCT DESCRIPTION: Recycled Rubber - Consist of Recycled Rubber mixed with a polyurethane binder.

2: PHYSICAL PROPERTIES

CHARACTERISTICS:	TEST RESULTS:	TEST METHOD
Density (Kg/m ³) (min)	550	ASTM F1315
Compressibility (%)	30 - 50	ASTM F36
Recovery (%) (min)	75	ASTM F36
Tensile strenght (Mpa) (min)	0,25	ASTM F152

3: TOLERANCE DIMENSIONS

	Nominal Value (mm)	Tolerance (mm)
Thickness	≤ 1,6 mm	± 0.25 mm
	> 1,6 ≤ 6 mm	± 0.38 mm
	> 6 ≤ 10 mm	± 0.5 mm
	> 10 ≤ 15 mm	± 0.75 mm
	≥ 15 mm	± 1 mm
Length		0 + 1 %
Width		± 1 %

4: VALUABLE INFORMATION

Storage

> The product should be kept at a temperature of 20 ± 3°C. and an Environmental relative humidity of 60 ± 5%.

Environmental Health and Safety

- > If properly used, this product is not know to be environmental harmful.
- > There are no special health danger when handling the product, however, powder filter mask and protection glasses should be used in the case of sawing cut, sanding operations, etc.

Corksribas – Indústria Granuladora de Cortiça, S.A.
 Rua do Fial (P.O. Box 22)
 4536-907 S. Paio de Oleiros Portugal
Tel: 00 351 227 459 007 | **Fax:** 00 351 227 642 959
email: global@corksribas.pt | **url:** www.corksribas.pt

DOC.GR.50.1