X-Tone Satin
Technical Specifications



Water-based colour-enhancing protective coating with a controlled satin finish. Gently revives the colour of ceramic and natural stone surfaces whilst preventing excessive shine.

Product description

X-Tone Satin is a water-based protective stain- and dirt-resistant impregnating agent with a controlled satin finish, used to slightly intensify the colour of textured ceramic or natural stone cladding whilst avoiding excessive shine.
The treated materials are protected against oil, grease, dirt, drinks, etc.
This application facilitates routine maintenance by reducing surface friction and preventing dirt from penetrating.
The product is UV-resistant and can therefore be used on both internal and external surfaces on dry materials.

Performance

Suitable for indoor and outdoor applications
It enhances the tone and colour of the surfaces to which it is applied
UV-resistant and weatherproof
Does not form a surface film
High penetration capacity
Excellent stain- and dirt-resistant properties
Water-based product exempt from transport hazard classifications

Uses

Suitable for treating medium-to-high absorbent surfaces and raw, textured or bush-hammered materials, such as natural stone (including aged stone), cobblestones and rough surfaces.

The product dries within a few hours and guarantees excellent long-term durability without forming a surface film.

Product specifications

Appearance	Liquid
Colour	White
Odour	Light
Customs heading	3824100010
Responsible packaging	1-litre recycled plastic bottles
Shelf life	24 months in the original packaging, away from heat sources and direct light.

Application Specifications

Working time	5–10 minutes
pH	8 - 9
Specific gravity	1.00 kg/l
Application	Brush, roller or pad
Permissible application temperatures	From +5°C to +35°C
Coverage	10–15 m^2/l

Application

Shake well before use.
On clean, dry surfaces, apply a thin, even coat of the undiluted product using a brush, roller or sponge.
Avoid leaving excess product on the surface; spread it evenly and allow it to dry.
Wait at least 2–3 hours after the first coat before applying a second coat using the same method.
Wait 4–6 hours after applying the final coat before opening to traffic.

Warnings

Apply at temperatures between +5°C and +35°C
Apply only to surfaces that are perfectly clean, dry and not overheated
Do not use on surfaces with a glossy, smooth or polished finish
When applying to recently laid or grouted surfaces, wait until the adhesive and grout have fully cured.
Before proceeding with application, it is advisable to carry out a preliminary test on a small section of the material to assess its suitability for the intended use
Do not use for applications not listed on this technical data sheet
For further information, please contact Litokol's Technical Customer Service on +39-0522-622811 or via customercare@litokol.com

Safety Information

For the safe use of our products, please refer to the latest version of the Safety Data Sheet, available at www.litokol.com
PRODUCT FOR PROFESSIONAL USE

Legal notices

The information and specifications contained in this technical data sheet are based on our best experience.
However, as we are unable to directly influence site conditions or the execution of the works, these are general guidelines which do not in any way bind our Company.
We therefore recommend carrying out a preliminary test to verify the product's suitability for the intended use; in any case, anyone intending to use it is required to determine whether or not it is suitable for the intended use and, in any event, assumes all liability that may arise from its use.
Always refer to the latest updated version of the Technical Data Sheet, available on the website www.litokol.com

Product details **No. 418**
Revision **No. 0**
Date: **06 25**

Litokol

Litokol Lab Spa Via G. Falcone 13/1 42048 Rubiera RE Italy
Tel. +39 0522 622811 info@litokol.com www.litokol.com